



N.V. DOTHÉE S.A.

# RD-FOOTBALL WHITE

## DESCRIPTION OF THE PRODUCT

USE:	Waterborne, onecomponent paint for the outlining of lawn sports grounds. Based on pure acrylic resin and titanium dioxide.
FEATURES:	The RD-Football White guarantees a high and durable whiteness index, due to the high degree of titanium dioxide contents – Easy to use.
SUBSTRATES:	Grass.
SYSTEM:	Apply the RD-Football White by means of a line marking machine, preferably on dry grass. The drawing of lines is possible on humid grass when the dilutions for the first lining are respected.  <u>First lining:</u> Dilute the RD-Football White, according to 1 volume of RD-Football White for 4 volumes of water. If necessary (depending on the used application means), prepare a mixture beforehand in a bucket.  <u>Refreshment of the lines:</u> Dilute the RD-Football White, according to 1 volume of RD-Football White for 6 volumes of water.

## APPLICATION INSTRUCTIONS

PREPARATION OF THE SUBSTRATE:	The substrate has to be dry (if humid, see the system above)
APPLICATION CONDITIONS:	Outdoor: never apply if raining Ambient temperature: > 5° C R.H.: max. 80 %
APPLICATION MEANS:	Line marking machine
DILUTION:	Water (see system)
CLEANING OF TOOLS:	Water, straight after the application
CONSUMPTION:	9 to 12 L of mixture for one football ground
PARTICULARITIES:	Mix well before use



**TECHNICAL DATA**

COLOURS:	White
SOLIDS CONTENT:	In weight: ca. 58 % In volume: ca. 41 %
VOC CONTENT:	Max 100 g/L
DENSITY:	Ca. 1.4
FLASH POINT:	Not flammable
VISCOSITY:	Ca. 30 P (Brookfield 20 Rpm)
DRYING TIME:	On touch: 2 hours (non-diluted)
PACKING:	5 L
STORAGE STABILITY:	12 months, keep away from heat and frost

**SAFETY DATA**

The safety data sheet is available on request.

These specifications are given for information. Since the manufacturer is not able to check the right application of the products, he cannot accept any responsibility for it. This technical data sheet replaces all previous editions.