



N.V. DOTHÉE S.A.

RD-ROOF COLOR

DESCRIPTION OF THE PRODUCT

USE:	One component coating can be applied on different types of roofs such as sloping roofs.
FEATURES:	Remains elastic even at low temperature. Overbridging cracks. Allows diffusion of water vapor. Unsaponifiable – alcali resistant. UV resistant. Doesn't discolour.. Perfect for masking imperfections. Easy to apply.
SUBSTRATES:	Suitable for roofs made of cement, asbeste, shingles etc.
SYSTEM:	Application with two coats, without primer, directly on the support, first coat has to be diluted with 10% water.

APPLICATIONS INSTRUCTIONS

PREPARATION OF THE SUBSTRATE:	<ol style="list-style-type: none"> 1. Clean the surface by using high pressure water. For cleaning moss use an appropriate anti-moss product. 2. The surface must be clean and dry. In case of sealing problems, call our technical service.
APPLICATION CONDITIONS:	By dry weather Ambient temperature: minimum 5° C R.H. : maximum 80 %
APPLICATION MEANS:	Brush, roller or airless spraying equipment (nozzle opening : 015 – 023)
DILUTION:	Water
CLEANING OF TOOLS:	Water
CONSUMPTION:	About 300 g/m ² in one coat depending on the degree of porosity of the backing.
PARTICULARITIES:	Mix well before use.

TECHNICAL DATA

FINISH:	Satin gloss
COLOURS:	See on the shade card – Roof Acryl New
DENSITY:	Ca 1.43
SOLIDS CONTENT:	Weight : ca. 65 % Volume : ca. 50 %
VOC CONTENT:	Max 30 g/L
FLASH POINT:	Not flammable
VISCOSITY:	150 – 200 P (Brookfield 20 Rpm)
DRYING TIME:	On touch: 3 hours Recoatable: after 6 hours
PACKING:	5 kg – 25 kg
STORAGE STABILITY:	12 months in a frost free place

SAFETY DATA

The safety sheet is available on request.

These specifications are given for information. Since the manufacturer is not able to check the right application of the products, he cannot accept any responsibility for it. This technical data sheet replaces all previous editions.