



N.V. DOTHÉE S.A.

RD-HYDROFUGE AQUA

DESCRIPTION OF THE PRODUCT

USE	Waterborne liquid solution of siloxane polymers for the water repelling protection of walls and façades, outdoor.
FEATURES	Protects against penetrating humidity - Lets breath the substrate - Almost doesn't change the aspect of the substrate - Very good outdoor durability.
SUBSTRATES	Bricks, concrete and other porous, mineral supports.
SYSTEM:	1 coat is enough for the slightly porous supports ; for the other ones, apply a second coat, wet on wet.

APPLICATION INSTRUCTIONS

PREPARATION OF THE SUBSTRATE:	The substrate has to be dry, degreased, and free of dust. Parts which doesn't be treated (glass or freestone) have to be protected against splashes.
APPLICATION CONDITIONS	Outdoor: by dry weather. Ambient temperature: > 5°C R.H.: max. 80%
APPLICATION MEANS	Brush or sprayed with a manual spray
DILUTION:	Don't dilute
CLEANING OF TOOLS:	Water.
CONSUMPTION :	Ca. 4 m ² /L per coat.
PARTICULARITIES	Mix well before use. Protect the parts which doesn't be treated.



TECHNICAL DATA

FINISH:	Little change of colours possible on some materials.
COLOURS :	Colourless
SOLIDS CONTENT :	In weight: min. 7 %
DENSITY:	Ca. 1.0
FLASH POINT:	Not flammable.
VISCOSITY:	15 sec. (Ford 4 – 23 °C)
DRYING TIME:	On touch: 1 hour Recoatable: wet on wet
PACKING:	1 L – 5 L – 20 L
STORAGE STABILITY:	12 months: keep away from heat.

SAFETY DATA

The safety data sheet is available on request.

These specifications are given for information. Since the manufacturer is not able to check the right application of the products, he cannot accept any responsibility for it. This technical data sheet replaces all previous editions.