



N.V. DOTHÉE S.A.

# RD-MUR ACRYL SOFT

## DESCRIPTION OF THE PRODUCT

USE:	Waterborne one component acrylic paint with soft finish, for outdoor walls. Very appropriate for different porous substrates.
FEATURES:	High covering capacity - Easy to apply because of a high percentage of binder - Permeable to vapours - Very good durability.
SUBSTRATES:	New and old masonry - Cement - Concrete.
SYSTEM:	<p>Untreated porous substrates:</p> <ul style="list-style-type: none"> <li>• Primer: 1 coat of impregnation RD-UNFIX;</li> <li>• Topcoat: 2 coats of RD-MUR ACRYL SOFT.</li> </ul> <p>Powdering painted substrates:</p> <ul style="list-style-type: none"> <li>• Primer: 1 coat of impregnation RD-UNFIX;</li> <li>• Topcoat: 1 or 2 coats of RD-MUR ACRYL SOFT.</li> </ul> <p>Not powdering painted substrates: direct application on the substrate of 1 or 2 coats of RD-MUR ACRYL SOFT.</p>

## APPLICATION INSTRUCTIONS

PREPARATION OF THE SUBSTRATE:	<p>The substrate has to be clean, dry, and free of dust.</p> <p>New masonries have to be cleaned first with an iron brush to eliminate all spatters of mortar. Painted supports should be cleaned with a high-pressure machine. If the substrate is mossy, the moss must be removed with a special anti-moss product.</p>
APPLICATION CONDITIONS:	<p>Outdoor: never apply if raining</p> <p>Ambient temperature: &gt; 5° C</p> <p>R.H.: max. 80 %</p>
APPLICATION MEANS:	Brush, roller or airless (nozzle: 013-018)
DILUTION:	Water
CLEANING OF TOOLS:	Water
CONSUMPTION:	7 à 10 m <sup>2</sup> /L per coat
PARTICULARITIES:	Mix well before use

**TECHNICAL DATA**

FINISH:	Soft
COLOURS:	White
SOLIDS CONTENT:	In weight: ca. 59 % In volume: ca. 45 %
VOC CONTENT:	Max 30g/L
DENSITY:	Ca. 1.4
FLASH POINT:	Not flammable
VISCOSITY:	100 - 150 P (Brookfield 20 Rpm)
DRYING TIME:	On touch: 2 hours Recoatable: 4 hours
PACKING:	1 L – 2.5 L – 4L – 10L – 20L
STORAGE STABILITY:	12 months, keep away from frost

**SAFETY DATA**

The safety data sheet is available on request.

These specifications are given for information. Since the manufacturer is not able to check the right application of the products, he cannot accept any responsibility for it. This technical data sheet replaces all previous editions.